

The logo for EHG, consisting of the letters "EHG" in a bold, blue, sans-serif font. A large, light gray arc is positioned behind the letters, starting from the left and curving upwards and to the right, partially enclosing the text.

All further Dimensions below 168,3mm Outer Diameter can possibly be manufactured on request!

[illegible]

All further Dimensions below 168,3mm Outer Diameter can possibly be manufactured on request!																				
	1	1,2	1,5	1,6	2	2,11	2,3	2,5	2,6	3	3,2	3,5	3,6	4	4,5	5	6	6,55	7,1	
83		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
84		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
85		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
88,9		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
90		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
93		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
95		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
100		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
101,6		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
103		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
104		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
106		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
108			X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
110			X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
114,3			X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
120			X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
123			X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
125			X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
127			X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
128			X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
129			X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
133			X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
139,7			X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
141			X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
153			X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
154			X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
156			X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
159			X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
168,3			X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X

Orange marked Dimensions can also be annealed

Standards: EN 10296-2 +AR +AT
 EN 10217-7 W0 / W1 / W2 / W1R / W2R /
 W0b / W1b / W2b / W1Rb / W2Rb
 EN 10357 CC / BC / CD / BD
 DIN 28181 TK1 / TK2
 EN 1127 D1 / D2 / D3 / D4
 T1 / T2 / T3 / T4 / T5
 SEW 470
 ASTM A249
 ASTM A312
 ASTM A778
 ASME SA249
 ASME SA312

Grades:

1.4301 AISI 304	1.4541 AISI 321
1.4306 AISI 304	1.4547 AISI 254SMO
1.4307 AISI 304L	1.4571 AISI 316 Ti
1.4401 AISI 316	1.4713 Sicromal 8
1.4404 AISI 316L	1.4720
1.4410 AISI F53	1.4828 AISI 309
1.4432 AISI 316L	1.4833 AISI 309S
1.4435 AISI 316L	1.4835 AISI 253 MA
1.4462 AISI 318LN	1.4841 AISI 314
1.4509 AISI 441	1.4845 AISI 310S
1.4510 AISI 439	1.4878 AISI 321H
1.4512 AISI 409	1.4948 AISI 304H
1.4529 AISI 926	1.4951 AISI 310S
1.4539 AISI 904L	more on request

Certificates: 3.1/EN 10204
 AD2000-W2 / AD2000-W10
 on Inquiry 3.2

Certifications: ISO9001
 DGRL2014/68/EU

Lengths: 100 - 15000 mm
 Tolerances <1 mm

Surface: Korn 180 / 240 / 320 / 400
 or with specified Ra-Value

Delivery Time 95 % of all Orders will be
 produced / delivered
 within 4 Weeks after Order

Order Sizes: Orders with all listed Options are possible,
 starting from a single coil length
 depending on specified wall thickness:

Wall Thickness	Coil Length
1mm	1000m
5mm	180m